



Technical Data	
Mains voltage/ power supply	230 V, 50 Hz
Rated frequency	1000 kHz
Pulse frequency	500 kHz
LF/HF leakage currents	as per IEC 60601-1, IEC 60601-2-2

Technical Data	
HF output power:	
Cutting current	50 W at 600 Ohm
Coagulation current	30 W at 1200 Ohm
Weight	2.8 kg
Dimensions	Height 78 mm Width 200 mm Depth 185 mm
CE marking	conform with 93/42/EEC

Ordering Information

80-006-02-04	KLS Martin MD 62 electrocautery unit with power cord, without accessories
--------------	---

80-106-01-04	Accessory set for MD 62 for foot switch operation, consisting of:
80-214-12-04	smartPen electrode handle without pushbutton, for 1.6-mm electrodes, with KLS Martin plug
80-444-08-01	Electrode box for 8 dental electrodes
80-461-01-04	Needle electrode Ø 0.2 mm, straight, Fig. 1
80-461-02-04	Needle electrode Ø 0.2 mm, 45° angled, Fig. 2
80-461-12-04	Wire loop electrode Ø 5.0 mm, Fig. 12
80-461-14-04	Wire loop electrode, rhombic, 8.0 x 5.0 mm, Fig. 14
80-461-15-04	Wire Loop electrode, elongated, 7.0 x 1.5 mm, shaft 45° angled, Fig. 15
80-461-31-04	Needle electrode for coagulation, Ø 0.6 mm, 45° angled, Fig. 31
80-812-10-04	Single-pedal foot switch, pneumatic, with connection tube of 3 m
80-505-00-04	Cleaning pad for electrodes, sterile packed, SU = 100/pack

80-107-00-04	Accessory set for MD 62 for hand switch operation, consisting of:
80-214-13-04	smartPen electrode handle with one pushbutton, for 1.6-mm electrodes, with KLS Martin plug
80-444-08-01	Electrode box for 8 dental electrodes
80-461-01-04	Needle electrode Ø 0.2 mm, straight, Fig. 1
80-461-02-04	Needle electrode Ø 0.2 mm, 45° angled, Fig. 2
80-461-12-04	Wire loop electrode Ø 5.0 mm, Fig. 12
80-461-14-04	Wire loop electrode, rhombic, 8.0 x 5.0 mm, Fig. 14
80-461-15-04	Wire loop electrode, elongated, 7.0 x 1.5 mm, shaft 45° angled, Fig. 15
80-461-31-04	Needle electrode for coagulation, Ø 0.6 mm, 45° angled, Fig. 31
80-505-00-04	Cleaning pad for electrodes, sterile packed, SU = 100/pack

KLS Martin Group

KLS Martin Australia Pty Ltd.
Sydney · Australia
Tel. +61 2 9439 5316
australia@klsmartin.com

KLS Martin do Brasil Ltda.
São Paulo · Brazil
Tel. +55 11 3554 2299
brazil@klsmartin.com

KLS Martin Medical (Shanghai) International Trading Co., Ltd
Shanghai · China
Tel. +86 21 5820 6251
china@klsmartin.com

KLS Martin India Pvt Ltd.
Chennai · India
Tel. +91 44 66 442 300
india@klsmartin.com

Martin Italia S.r.l.
Milan · Italy
Tel. +39 039 605 67 31
italia@klsmartin.com

Nippon Martin K.K.
Tokyo · Japan
Tel. +81 3 3814 1431
nippon@klsmartin.com

KLS Martin SE Asia Sdn. Bhd.
Penang · Malaysia
Tel. +604 506 2380
malaysia@klsmartin.com

KLS Martin de México S.A. de C.V.
Mexico City · Mexico
Tel. +52 55 7572 0944
mexico@klsmartin.com

Martin Nederland/Marned B.V.
Huizen · Netherlands
Tel. +31 35 523 45 38
infol@klsmartin.com

Gebrüder Martin GmbH & Co. KG
Moscow · Russia
Tel. +7 499 792 76 19
russia@klsmartin.com

KLS Martin Taiwan Ltd.
Taipei 106 · Taiwan
Tel. +886 2 2325 3169
taiwan@klsmartin.com

Gebrüder Martin GmbH & Co. KG
Dubai · United Arab Emirates
Tel. +971 4 454 16 55
middleeast@klsmartin.com

KLS Martin UK Ltd.
Reading · United Kingdom
Tel. +44 118 467 1500
uk@klsmartin.com

KLS Martin LP
Jacksonville · Florida, USA
Tel. +1 904 641 77 46
usa@klsmartin.com

KLS martin
GROUP



Do you know how to get all important information about the KLS Martin Energy Devices?

Please download KLS Martin App Energy Devices! The App is available for Android and iOS.



<https://itunes.apple.com/de/app/kls-martin-energy-devices/id1198171415?l=de&ls=1&mt=8>



<https://play.google.com/store/apps/details?id=com.klsmartin.energy-devices>

Gebrüder Martin GmbH & Co. KG
A company of the KLS Martin Group

KLS Martin Platz 1 · 78532 Tuttlingen · Germany
P.O. Box 60 · 78501 Tuttlingen · Germany
Tel. +49 7461 706-0 · Fax +49 7461 706-193
info@klsmartin.com · www.klsmartin.com

MD 62

The compact electrocautery unit built to high safety standards

MD 62

The compact electrosurgical unit built to high safety standards

The KLS Martin MD 62 is an electrosurgical unit for use in dentistry. Additional fields of application include dermatology and minor cosmetic surgery.



KLS Martin MD 62

HF surgery is considered a safe and proven method in dentistry. With its special features and accessories and matching output power, KLS Martin's MD 62 electrosurgical unit meets all requirements in this field.

Thanks to its small dimensions, the unit is very easy to handle, providing maximum flexibility in use.

The KLS Martin MD 62 has the following main features:

- Two different types of current, one for cutting and one for coagulation.
- To account for the special conditions and requirements associated with dental, oral and maxillomandibular applications, the high-frequency current can be activated in two different ways. In hand switch mode, the HF current is activated via a finger-operated switch located on the handle. In foot switch mode, a handle without a pushbutton is used and the HF current is activated via a foot switch.
- An optional foot switch is available for use with a handle without pushbutton.
- The powerful electrosurgical unit is supplemented by a wide range of high-quality electrodes and accessories.

Safe and Easy Operation

All functions available are clearly marked by symbols on the front panel. The unit features an analog rotary switch for safe and easy power setting. The two types of current can be activated – at the user's option – either via a foot switch or a handle featuring a pushbutton.

All connector jacks are marked unambiguously for correct use.

Safety in Use

The KLS Martin MD 62 has been designed to meet the high demands of surgical users.

The device carries the CE mark according to the directive 93/42/EEC of 14.06.1993 of medical devices.

Due to the monoterminal technique, no neutral electrode is needed. This spares the patient the inconvenience caused by NE attachment.

Performance Characteristics

The user has two types of current available: one for cutting and one for coagulation. These currents have been matched to the tissue-specific impedances involved and are fully compatible with the monoterminal mode of operation.

This powerful electrosurgical device provides the high technical quality, reliability and safety medical specialists require in daily practice.

Hygiene Made Easy

The housing is made of high-quality, coated sheet steel. This reliably prevents oxidation caused by disinfectants.

As neither cooling slots nor fans are required for safe operation, no liquids such as cleaning or disinfecting solutions can penetrate into the unit.

Wide Range of High-Quality Accessories

Handles specially optimized for use in the oral cavity plus a comprehensive range of active electrodes guarantee the unit's usefulness and reliability in daily practice.

Selected accessories have been combined into a practical set.

Application examples from dentistry:

- gingivoplasty/gingivectomy
- dentitis difficilis
- hemostasis by using HF current (electrocoagulation)
- biopsy
- tumor resection/coagulation
- root canal sterilization
- mucosal surgery (removal of abscesses, overgrowth, fibromas)
- lengthening of tooth crowns or abutment teeth that are too short for bridge support
- surgical treatment of abnormal labial or lingual frenula
- desensitization of bare dental necks